

» **Info hotline**

Any questions? We would love to help. Call us on
0800 7020700.

» **Our trade partners**

Our competent local contacts will assist you if you
have any questions.



Type				
Type	HTT 4 WS	HTT 5 WS	HTT 5 AM	HTT 5 SM
Part no.	074464	074465	182052	182053
Connection output	2,60 kW	2,60 kW	2,60 kW	2,60 kW
Height	250 mm	266 mm	266 mm	266 mm
Width	238 mm	257 mm	257 mm	257 mm
Depth	230 mm	230 mm	230 mm	230 mm
Specification				
Power connection	1/N 220-240 V 50/60 Hz	1/N 220-240 V 50/60 Hz	1/N 220-240 V 50/60 Hz	1/N 220-240 V 50/60 Hz
Weight	2,70 kg	4,20 kg	4,20 kg	4,20 kg
Colour	alpine white	off white, RAL 9003	anthracite metallic	silver metallic
Casing material	Plastic	Diecast aluminium	Diecast aluminium	Diecast aluminium
Air flow rate	250 m³/h	250 m³/h	250 m³/h	250 m³/h
IP-Rating	IP23	IP23	IP23	IP23
Protection class	II	II	II	II

HTT turbotronic hand dryer

Dry in a jiffy.

The HTT series of hand dryers are the most powerful. Their enormous air flow rate enables them to deliver especially quick drying times. Their powerful output means that they rank amongst the fastest, most economical and hygienic hand dryers. Such features make HTT dryers particularly suitable for public toilets and swimming baths and other places where there are high usage rates, such as railway stations, airports and bars/restaurants. All HTT models operate with an electronic IR proximity sensor. This switches the hand dryer ON when your hands are placed 6 to 12 cm below the air outlet, and OFF again when you remove your hands. The robust casing is made of diecast aluminium with a tough paint finish that ensures it retains its hygienic look over its long service life.



The most important features

2500 W output

HTT 4 with casing made from impact-resistant plastic

HTT 5 with a diecast aluminium casing

Air flow rate 250 m³/h

220 - 240 V

Operating noise 68 dB(A)

HTT 4 in alpine white

HTT 5 in signal white, anthracite metallic or silver metallic